




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6 : B03C 3/155	A1	(11) International Publication Number: WO 98/22222 (43) International Publication Date: 28 May 1998 (28.05.98)
(21) International Application Number: PCT/SE97/01950 (22) International Filing Date: 20 November 1997 (20.11.97) (30) Priority Data: 9604279-1 21 November 1996 (21.11.96) SE (71) Applicant (for all designated States except US): BLUE AIR AB [SE/SE]; Danderydsgatan 11, S-114 26 Stockholm (SE). (72) Inventor; and (75) Inventor/Applicant (for US only): WENNERSTRÖM, Johan [SE/SE]; Ebba Brahes väg 9B, S-192 69 Sollentuna (SE). (74) Agent: ERIKSSON, Kjell; Norrtälje Patentbyrå AB, P.O. Box 38, S-761 21 Norrtälje (SE).		(81) Designated States: AL, AM, AT, AT (Utility model), AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, CZ (Utility model), DE, DE (Utility model), DK, DK (Utility model), EE, EE (Utility model), ES, FI, FI (Utility model), GB, GE, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (Utility model), TJ, TM, TR, TT, UA, UG, US, UZ, VN, ARIPO patent (GH, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i> <i>In English translation (filed in Swedish).</i>
(54) Title: DEVICE IN CONNECTION WITH AN ELECTROSTATIC FILTER (57) Abstract The invention relates to a device in connection with an electrostatic filter for air purifying, said filter including an ionizing portion (1) and a precipitating portion (2). The precipitating portion (2) consists of a unit (10) that is composed of at least one non-conductive or partly conductive air permeable layer (12), provided between at least two proximate, conductive or partly conductive, air permeable layers (11, 13), one (11) of said layers having a higher potential than the other (13), an electrical field being present between the layers (11, 13) in order to collect particles in an air stream that is transported through the precipitating portion (2). 		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

DEVICE IN CONNECTION WITH AN ELECTROSTATIC FILTER

The present invention relates to a device in connection with an electrostatic filter for air purifying, said filter including a ionizing portion and a precipitating portion.

5 An electrostatic filter is usually composed of two portions, i.e. an ionizing portion where particles are charged, said particles being transported by an air stream through the filter, and a precipitating portion where the charged particles are separated from the air. The ionizing
10 portion may consist of a corona wire located between two target electrodes, a high voltage potential is applied to the corona wire and a lower potential to the target electrodes. At a sufficient high potential applied to the wire a so called corona discharge occurs around said corona wire. At this
15 discharge ions are released from the wire and said ions find their way to the target electrodes. The precipitating portion normally consists of parallel plates, i.e. a so called precipitator, and every second plate has high voltage potential and every second low. This generates an electrical
20 field between the plates. A particle carried by the air through the filter passes initially the ionizing portion and then collides with one or more ions and is thus charged. When the charged particle passes the precipitator it is affected by the electrical field and its path is curved towards one of the
25 plates and is deposited upon said plate. The benefit of these filters is low pressure drop and high separation degree for small particles. The disadvantage on the other hand is a complicated structural design, low dust collecting ability, i.e. short service intervals, and that large, i.e. heavy
30 particles may pass directly through without being separated.

As regards mechanical filters it is meant in this connection a filter that "screens" the air passing through the filter. The filter media often consists of a porous bed of fibres of e.g. glass or syntetic material. Among other things
35 the diameter of the fibres and the density between the fibres are determinant for the performance of the filter. Generally small fibres having small space between the fibres result in a filter media that has high separation degree for small particles. However, the pressure drop across the filter media

increases by increased density. The advantage with this type of filter is high dust collecting ability and high separation degree but the disadvantage is high pressure drop.

As regards electret filters is meant a mechanical filter as defined above with the difference that the fibres have a "permanent" charging. The consequence of this is that a relatively coarse filter having thick fibres and consequently low pressure drop may separate small particles, if said particles have a low charging. The charging of the fibres decline eventually and the performance of the filter also declines. The advantages with this type of filter is a high initial separation degree and relatively low pressure drop but the disadvantages is that the separation degree declines after a certain time of use.

The aim of the present invention is to provide a device in connection with an electrostatic filter, said device eliminating the disadvantages of the above mentioned, previously known filters. The characterising features of the invention are defined in the appended claims.

Thanks to the device according to the present invention a filter has been provided that in a proper way realises its aims and is simultaneously simple and cheap to manufacture. The electrostatic filter for air purifying according to the invention is composed of an ionizing portion and a precipitating portion, where the ionizing portion may be designed in a conventional way by e.g. a corona wire or a coal fibre brush or the like and where the ionizing may be located directly adjacent to the precipitating portion, this is however not necessary. In the structural design of the precipitating portion there is a non-conductive or to a certain degree air permeable layer located between two conductive or partly conductive air permeable layers. One of the conductive layers are kept at a higher potential than the other, whereby an electrical field is generated between said layers, and thus a charged particle that is carried by an air stream through the filter is affected by the electrical filter between the two conductive layers. The path of the particle is then irregular and the particle adhere to the layer. The advantage of this filter design is that a simple coarse filter

medium may be used for separating small particles. The filter medium may be washable and e.g. constitute of a polyester foam having open pores. Further advantages are that there is a low pressure drop across the filter compared to mechanical filters and electret filters and high separation degree and high dust collecting ability compared to electrostatic filters and a simple design and consequently simple manufacturing.

The invention is described more in detail below by the aid of a preferred embodiment and reference to the enclosed drawings, where

- Figure 1 shows a schematic view of a previously known two-step electrostatic filter including an ionizing portion and a precipitating portion;
- Figure 2 shows a precipitating portion according to the present invention, that may correspond to the precipitating portion in figure 1; and
- Figure 3 shows an alternative embodiment of the precipitating portion disclosed in figure 2 including a filter designed in several layers, i.e. including four layers of filter media and five conductive layers.

In figure 1 is shown a schematic view of a previously known electrostatic filter for air purifying. The filter is composed of an ionizing portion 1 and a precipitating portion 2. The ionizing portion 1 may be constituted of a corona wire 3 located between two target electrodes 4 and 5. A high voltage potential may be applied to the corona wire and a lower potential to the target electrodes 4, 5, a corona discharge occurs at a sufficient high potential applied to the wire 3. During this discharge ions are released from the wire 3 and said ions find their way to the target electrodes 4 and 5. The precipitating portion 2 normally constitutes of parallel plates, so called precipitators, where every second plate 6, 8 has a high voltage potential and every second plate 7, 9 has a low voltage potential, this generating an

electrical field between the plates. A particle that by an air stream is carried through the filter passes initially the ionizing portion 1 and collides with one or more ions and is consequently charged and, when said particle passes the precipitating portion 2, it is affected by the electrical field and its path is curved towards one of the plates for deposition upon said plate.

The filter according to the present invention may be designed according to figure 1 having an ionizing portion 1 and a precipitating portion 2, where the ionizing portion may be designed in the shown conventional way with a corona wire 3 or a coal fibre brush but the ionizing portion must not be located in close proximity to the precipitating portion 2. The precipitating portion 2 is however designed as is shown more in detail in figure 2, where this portion consists of a unit 10 that is composed of at least one non-conductive or partly conductive air permeable layer 12 provided between two adjacent, conductive or partly conductive, air permeable layers 11, 13, one layer 11 having a higher potential than the other layer 13, and that an electrical field is present between the layers 11, 13 in order to have a charged particle that is transported by an air stream through the filter affected by said electrical field between said two conductive layers 11, 13, said path of the article through the layer 12 being irregular and the particle adhering to said layer.

The conductive or partly conductive layers 11, 13 may be designed in several ways. They may consist of grilles or metal wires, expanded metal, applied, conductive fibres of different conductive materials and so on. The layer 12 may consist of different materials and have different structures. It may consist of a mechanical filter medium manufactured from fibres of glass or plastic, foam materials having open pores and so on.

The filter unit 10 according to the invention may also be designed having several layers as can be seen from figure 3. In said figure a filter is disclosed having four layers, as filter media conductive layers 14-17 and five conductive layers 18-22 adjoining said layers 14-17, every second 18, 20,

22 of the conductive layers having a higher potential than the rest of the layers 19 and 21.

The non-conductive or semi-conductive layers may also consist of a material that simultaneously serves as a deposition surface for particles and for reduction of gases in the air. The material in the layer may in such cases e.g. consist of fibres of activated carbon. The filter according to the invention may be voltage-fed either in an "active way" or in a "passive way". By active way is meant direct coupling of the layers 11, 13 or 18-22 to a voltage source. By passive way is meant that the layers 11, 13 or 18-22 are charged by the upstream ionizing portion. The first layer upstream of the filter may then serve as target electrode for the ionizing portion.

According to an alternative embodiment of the invention at least one of the conductive or partly conductive air permeable layers 11, 13; 18, 19, 20, 21, 22 may include a gas adsorbing material, preferably activated carbon. By such an arrangement the effect is achieved that apart from particle separation of the air passing through the filter 12/the filters 14, 15, 16, 17 also a separation of gaseous pollutions takes place. By designing both the conductive and partly conductive air permeable layers 1, 13; 18, 19, 20, 21, 22 to include a gas adsorbing material, i.e. the layers located on both sides of the filter 12/filters 14, 15, 16, 17 the separation degree and capacity as regards gaseous pollutions are increased.

Also by this alternative embodiment, i.e. when thus the conductive or partly conductive, air permeable layers 11, 13; 18, 19, 20, 21, 22 preferably include activated carbon said layers may be designed in a way that is described on top of page 5, i.e. such a grille may be coated with activated carbon. It should especially be mentioned that when the filter 12/the filters 14, 15, 16, 17 consist of a so called coarse filter medium, activated carbon may be applied to said coarse filter medium, e.g. by having the coarse filter medium dipped into a suspension of activated carbon in powder form, adhesive and water. Thus both sides of the coarse filter medium is normally coated with activated carbon. If it is wished that

only one side of the coarse filter medium is coated with activated carbon alternative coating techniques may be used.

Claims

1. Device in connection with an electrostatic filter for air purifying, said filter including an ionizing portion (1) and a precipitating portion (2), c h a r a c t e r i z e d in that the precipitating portion (2) consists of a unit (10) that is composed of at least one non-conductive or partly conductive air permeable layer (12), provided between at least two proximate, conductive or partly conductive, air permeable layers (11, 13), one (11) of said layers having a higher potential than the other (13), an electrical field being present between the layers (11, 13) in order to collect particles in an air stream that is transported through the precipitating portion (2).
2. Device according to claim 1, c h a r a c t e r i z e d in that the conductive layers (11, 13) consist of grilles or metal wires, expanded metal, applied fibres of different conductive materials.
3. Device according to claim 1, c h a r a c t e r i z e d in that the precipitating portion (2) includes four layers (14-17) serving as filter medium and five conductive layers (18-22) adjoining said filter medium layers (14-17), every second (18, 20, 22) of said conductive layers having higher potential than the rest of the layers (19, 21).
4. Device according to anyone of the preceding claims, c h a r a c t e r i z e d in that the non-conductive or partly conductive layer (12, 14-17) has a mechanical filter medium manufactured from glass or plastic or from a foam material having open pores.
5. Device according to anyone of the preceding claims, c h a r a c t e r i z e d in that the precipitating portion (2) is fed in an active way by direct coupling to the layers (11, 13, 18-22) to a voltage source or is fed in a passive way by charging from the upstream ionizing portion.

6. Device according to anyone of the claims 1-5, characterized in that at least one of the conductive or partly conductive, air permeable layers (11, 13) include a gas adsorbing material.

5

7. Device according to claim 6, characterized in that the gas adsorbing material consists of activated carbon.

8. Device according to claim 7, characterized in
10 that the activated carbon is in powder form, that in suspension is applied to the non-conductive or partly conductive, air permeable layer (12).

Fig 1




Fig 2





Fig 3



SUBSTITUTE SHEET (RULE 26)

1
INTERNATIONAL SEARCH REPORT

International application No.
PCT/SE 97/01950

A. CLASSIFICATION OF SUBJECT MATTER

IPC6: B03C 3/155

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC6: B03C

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 9311876 A1 (YAMAMOTO, YUJIRO), 24 June 1993 (24.06.93), page 5, line 14 - page 7, line 11	1-5
Y	--	6-8
X	US 2822058 A (WILLIAM J. ROOS ET AL), 4 February 1958 (04.02.58), figure 1, claims 1,2	1,2,4,5
X	US 3800509 A (ALLAN W. CARR ET AL), 2 April 1974 (02.04.74), column 1, line 35 - line 49, figure 11	1,2,4,5
Y	US 5108470 A (WILLIAM PICK), 28 April 1992 (28.04.92), claims 3,4, abstract	6-8

☐ Further documents are listed in the continuation of Box C.

☒ See patent family annex.

* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

6 March 1998

Date of mailing of the international search report

11-03-1998

Name and mailing address of the ISA/
Swedish Patent Office
Box 5055, S-102 42 STOCKHOLM
Facsimile No. +46 8 666 02 86

Authorized officer

Ulf Nyström
Telephone No. +46 8 782 25 00

Form PCT/ISA/210 (second sheet) (July 1992)

INTERNATIONAL SEARCH REPORT
Information on patent family members

International application No.

PCT/SE 97/01950

Patent document cited in search report			Publication date	Patent family member(s)		Publication date
WO	9311876	A1	24/06/93	AU	3233093 A	19/07/93
				CA	2117335 A	24/06/93
				JP	7501745 T	23/02/95
				US	5368635 A	29/11/94
				US	5540761 A	30/07/96

US	2822058	A	04/02/58	NONE		

US	3800509	A	02/04/74	AR	195589 A	23/10/73
				AU	462598 B	26/06/75
				AU	4974572 A	13/06/74
				CH	548796 A	15/05/74
				DE	2301044 A,B,C	23/08/73
				FR	2172198 A,B	28/09/73
				GB	1407070 A	24/09/75
				JP	48089457 A	22/11/73
				NL	7300558 A	16/08/73
				SE	385194 B,C	14/06/76
				ZA	7208624 A	29/08/73

US	5108470	A	28/04/92	CA	1314237 A	09/03/93

Form PCT/ISA/210 (patent family annex) (July 1992)

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

☐ BLACK BORDERS

☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES

☐ FADED TEXT OR DRAWING

☒ BLURRED OR ILLEGIBLE TEXT OR DRAWING

☐ SKEWED/SLANTED IMAGES

☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS

☐ GRAY SCALE DOCUMENTS

☐ LINES OR MARKS ON ORIGINAL DOCUMENT

☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY

☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.